

PSA LifeSaver

LIFPE9M

Photoelectric smoke alarm
operated by a 9V battery



Perfect for caravans, small homes and rental properties requiring a smoke alarm that complies to AS3786:2014. The PSA Lifesaver LIFPE9M is a standalone 9V battery operated photoelectric smoke alarm that can be easily surface mounted to any wall or ceiling.

Features

Compact Size

The compact size of the LIFPE9M makes it perfect for use in caravans, motor homes, small homes or apartments and is perfect for rental properties.

Easy Twist Operation

Installing the LIFPE9M is easy, simply attach the mounting plate to the wall or ceiling and twist the alarm to the mounting bracket.

Easy Maintenance

Maintaining the alarm is simple, just twist the alarm off, replace the battery and clean the alarm, shortening the time smoke alarm maintenance teams need to service the home.

Single Button Test and Hush

In the case of a false alarm, the single test hush button allows the user to silence the alarm for up to 10 minutes. When pushed and held, the test hush button will also trigger the alarm, allowing maintenance staff users to test the alarm periodically.

Fully Compliant

The LIFPE9M is fully certified and compliant to the latest Australian standard for smoke alarms, AS3786:2014. Like all PSA products, the LIFPE9M has been rigorously tested by our factory, which means you can sleep easy knowing the PSA Lifesaver LIFPE9M is keeping your family PSA Safe.

2 Year
Warranty

Specifications

Power	9V Battery
Warranty	2 years
Operating temperature	0°C to 45°C
Dimensions	90mm Diameter x 35mm High.
Approvals	AS3786:2014
Sensor Type	Photoelectric
Battery Backup	9V Battery
Alarm Volume	85db at 3 metres
Alarm Signal Pattern	ISO8201 ((T3 - Repeat 3 long beeps))
Humidity Range	10% - 90%
Alarm Duration	As long as smoke is present, resets when smoke clears
Alarm Indication	Flashing red LED
Indicator LED	Red LED Flashes rapidly during alarm. Flashes every 32 seconds in normal operation.
Low Battery Indication	"Chirp" every 32 seconds
Mute Function	When in Mute mode, the unit is desensitised for 10 minutes.
Mute Indication	Red LED Flash every 8 seconds for 10 minutes, then resets.



Tested & Complies to
Australian Standards
AS3786:2014

Item Code	Single	Pack	Carton
Quantity	1	20	60
Barcode	9318475030165	19318475030162	29318475030169

