Resil Brazil fire extinguisher BE powder

| Nesii Brazii ille extiliguisher BL powder |  |                     |                     |
|---|--|---------------------|---------------------|
| Fire Extinguisher                         | Dry Chemical BE  | Dry Chemical BE     | Dry Chemical BE     |
| ABE DRY CHEMICAL Fire<br>Extinguishers    | The BE DRY CHEMICAL fire extinguisher can be safely used on fires involving live electrical equipment or flammable liquids. It is especially effective on cooking oil fires. |                     |                     |
| Size (Capacity)                           | 2.3KG  | 4.5KG               | 9.0KG               |
| Part Number                               | FW2.3BE  | FW4.5BE             | FW9.0BE             |
| Powder Type                               | Kidde ABC 70   | Kidde ABC 70        | Kidde ABC 70        |
| Tare Weight                               | 3.2KG  | 7.5KG               | 13KG                |
| Fire Rating                               | 20BE   | 40BE                | 80BE                |
| Aust Standard Approval                    | AS/NZ 1841-5   | AS/NZ 1841-5        | AS/NZ 1841-5        |
| SAI Licence Number                        | SMK 0357   | SMK 0357            | SMK 0357            |
| Dimensions: Height                        | 400mm  | 500mm               | 565mm               |
| Dimensions: Depth                         | 124mm  | 160mm               | 180mm               |
| Dimensions: Width                         | 173mm  | 250mm               | 265mm               |
| Discharge time                            | 14 seconds   | 18 seconds          | 26 seconds          |
| Effective Range                           | 3 metres   | 5 metres            | 5 metres            |
| Operating Pressure                        | 1035 KPA   | 1345 KPA            | 1345 KPA            |
| Propellant                                | Dry Nitrogen   | Dry Nitrogen        | Dry Nitrogen        |
| Periodic Pressure Test                    |  |                     |                     |
| :Normal Conditions                        | 5 Years  | 5 Years             | 5 Years             |
| :Aggressive Environment                   | 3 Years  | 3 Years             | 3 Years             |
| Materials : Valve                         | Nickel Plated Brass  | Nickel Plated Brass | Nickel Plated Brass |
| : Cylinder                                | Mild Steel   | Mild Steel          | Mild Steel          |
| : Cylinder Finish                         | Power Coated   | Power Coated        | Power Coated        |
|   |  |                     |                     |

